

Tensor DL non-transducerized screwdrivers exist in two different tool configurations:

**ETP** – Pistol grip handle screwdrivers with configurable function button. Available as lever and push to start.

**ETF** – Straight screwdrivers for fixtured applications. Configurable lever or remote start.

- The DL screwdriver range has been optimized for small screw assembly.
- Torque range up to 10 Nm.
- All tools have ESD certification.
- Ergonomic design promotes operator safety.
- Brushless motor gives long service intervals and low maintenance costs.
- Signal lights ensure detection of incorrectly tightened fasteners.



ETF DL



ETP DL

Model	Torque range		Speed r/min	Weight		Length mm	CS distance mm	Ordering No.
	Nm	in lb		kg	lb			
<b>Pistol grip, lever start</b>								
ETP DL21-04-I06	1-4	8.8-35.4	1600	0.6	1.3	235	20	8433 4024 19
ETP DL21-07-I06	2.2-7.5	19.5-66	970	0.6	1.3	235	20	8433 4027 26
ETP DL21-10-I06	3-10	26.6-88.5	720	0.6	1.3	235	20	8433 4029 13
<b>Pistol grip, push-to-start and front lights</b>								
ETP DL21-01-I06-PS-H	0.3-1.2	2.6-10	2200	0.6	1.3	243	20	8433 4020 77
ETP DL21-04-I06-PS-H	1-4	8.8-35.4	1600	0.6	1.3	243	20	8433 4024 66
ETP DL21-07-I06-PS-H	2.2-7.5	19.5-66	970	0.6	1.3	243	20	8433 4027 53
ETP DL21-10-I06-PS-H	3-10	26.6-88.5	720	0.6	1.3	243	20	8433 4029 28
<b>Fixtured tools, lever start or remote start</b>								
ETF DL21-01-I06-T25	0.3-1.2	2.6-10	2200	0.7	1.5	328	18 / 19.5	8433 4040 04
ETF DL21-04-I06-T25	1-4	8.8-35.4	1600	0.7	1.5	328	18 / 19.5	8433 4042 13
ETF DL21-07-I06-T25	2.2-7.5	19.5-66	970	0.7	1.5	328	18 / 19.5	8433 4043 22
ETF DL21-10-I06-T25	3-10	26.6-88.5	720	0.7	1.5	328	18 / 19.5	8433 4044 11