

# Riveting Hammers



- Wide range of hammers suitable for all applications.
- Recoilless series for better operator's comfort.
- Progressive trigger for better control.

## How to select the right tool?

|  |   |  |   |
|--|---|--|---|
|  |   |  |   |
| <p><b>1</b><br/>Rivet<br/>Light/Hard Material<br/>Diameter</p> | <p><b>2</b><br/>Application<br/>accessibility</p> | <p><b>3</b><br/>Operation repetitiveness<br/>Low vibration level</p> | <p><b>4</b><br/>Rivet set<br/>selection</p> |

## Tool range

Our range covers a wide range of applications to answer all your requirements



# Riveting Hammers

## Selection guide



| PIC REF | MODEL | PART NUMBER | AIR FRAME REF | BLOW PER MINUTE | BORE & STROKE |   | ENERGY PER BLOW |    | CHISEL SHANK |          | RIVET CAPACITY |    | WEIGHT |     | AIR INLET | HOSE INT. Ø |  |
|---------|-------|-------------|---------------|-----------------|---------------|---|-----------------|----|--------------|----------|----------------|----|--------|-----|-----------|-------------|--|
|         |       |             |               |                 | mm (in.)      | J | ft.lb           | mm | in.          | mm (in.) | mm (in.)       | kg | lb     | in. | mm        | in.         |  |

### Standard

|   |              |               |              |      |                                 |      |      |      |       |               |               |     |     |     |    |     |
|---|--------------|---------------|--------------|------|---------------------------------|------|------|------|-------|---------------|---------------|-----|-----|-----|----|-----|
| A | CP4444-1     | 205 147 938 4 | 2X<br>(200)  | 2580 | 15 x 40<br>(19/32 x 1.47)       | 4.4  | 3.2  | 10.2 | 0.401 | 3.2<br>(1/8)  | 2.4<br>(3/32) | 1.2 | 2.6 | 1/8 | 10 | 3/8 |
| B | CP4444-RURAB | T022961       | 2X<br>(200)  | 2580 | 12.7 x 50.8<br>(1/2 x 2)        | 4.0  | 2.9  | 10.2 | 0.401 | 3.2<br>(1/8)  | 2.4<br>(3/32) | 1.0 | 2.2 | 1/4 | 10 | 3/8 |
| B | CP4444-RUSAB | T022962       | 3X<br>(300)  | 2160 | 12.7 x 76.2<br>(1/2 x 3)        | 6.1  | 4.5  | 10.2 | 0.401 | 4.8<br>(3/16) | 4.0<br>(5/32) | 1.1 | 2.3 | 1/4 | 10 | 3/8 |
| B | CP4444-RUTAB | T022963       | 4X<br>(240)  | 1740 | 12.7 x 101.6<br>(1/2 x 4)       | 8.1  | 6.0  | 10.2 | 0.401 | 6.4<br>(1/4)  | 4.8<br>(3/16) | 1.3 | 2.7 | 1/4 | 10 | 3/8 |
| C | CP4447-RUSAB | T022965       | 5XB<br>(500) | 1560 | 19.1 x 68.3<br>(3/4 x 2-11/18)  | 12.3 | 9.1  | 12.7 | 0.498 | 6.4<br>(1/4)  | 4.8<br>(3/16) | 2.2 | 4.7 | 1/4 | 10 | 3/8 |
| C | CP4447-RUTAB | T022912       | 7XB<br>(700) | 1140 | 19.1 x 98.4<br>(3/4 x 3-7/8)    | 17.8 | 13.1 | 12.7 | 0.498 | 7.9<br>(5/16) | 6.4<br>(1/4)  | 2.3 | 5.1 | 1/4 | 10 | 3/8 |
| C | CP4447-RUVAB | T022964       | 9XB<br>(800) | 900  | 19.1 x 147.6<br>(3/4 x 5-13/16) | 26.6 | 19.6 | 12.7 | 0.498 | 9.5<br>(3/8)  | 7.9<br>(5/16) | 2.7 | 9.0 | 1/4 | 10 | 3/8 |

### Vibration reduced

|   |          |         |              |      |                           |      |      |      |       |               |               |     |     |     |    |     |
|---|----------|---------|--------------|------|---------------------------|------|------|------|-------|---------------|---------------|-----|-----|-----|----|-----|
| D | CP4450-2 | T025189 | 2X<br>(200)  | 2580 | 12.7 x 50.8<br>(1/2 x 2)  | 4.0  | 2.9  | 10.2 | 0.401 | 3.2<br>(1/8)  | 2.4<br>(3/32) | 1.2 | 2.7 | 1/4 | 10 | 3/8 |
| D | CP4450-3 | T025190 | 3X<br>(300)  | 2160 | 12.7 x 76.2<br>(1/2 x 3)  | 6.1  | 4.5  | 10.2 | 0.401 | 4.8<br>(3/16) | 4.0<br>(5/32) | 1.3 | 2.8 | 1/4 | 10 | 3/8 |
| D | CP4450-4 | T025191 | 4X<br>(400)  | 1740 | 12.7 x 101.6<br>(1/2 x 4) | 8.1  | 6.0  | 10.2 | 0.401 | 6.4<br>(1/4)  | 4.8<br>(3/16) | 1.5 | 3.2 | 1/4 | 10 | 3/8 |
| E | CP4475-3 | T025241 | 5XB<br>(500) | 2000 | 19.1 x 76.2<br>(3/4 x 3)  | 13.7 | 10.1 | 12.7 | 0.498 | 6.4<br>(1/4)  | 4.8<br>(3/16) | 1.8 | 3.9 | 1/4 | 10 | 3/8 |
| E | CP4475-4 | T025242 | 7XB<br>(700) | 1700 | 19.1 x 101.6<br>(3/4 x 4) | 18.3 | 13.5 | 12.7 | 0.498 | 7.9<br>(5/16) | 6.4<br>(1/4)  | 2.4 | 5.3 | 1/4 | 10 | 3/8 |
| E | CP4475-6 | T025243 | 9XB<br>(800) | 1250 | 19.1 x 152.4<br>(3/4 x 6) | 27.5 | 20.3 | 12.7 | 0.498 | 9.5<br>(3/8)  | 7.9<br>(5/16) | 2.8 | 6.2 | 1/4 | 10 | 3/8 |

\* LIGHT: Aluminium 2017 / 2117 (DCJ-DXJ / D-AD)

\*\* HARD: Aluminium 7050 (DKJ / KE / E) (M) (T)

## Dimensions

| Model        | A   |      |
|--------------|-----|------|
|              | mm  | in.  |
| CP4444-1     | 111 | 4.4  |
| CP4444-RURAB | 170 | 6.7  |
| CP4444-RUSAB | 186 | 7.3  |
| CP4444-RUTAB | 211 | 8.3  |
| CP4447-RUSAB | 227 | 8.9  |
| CP4447-RUTAB | 252 | 9.9  |
| CP4447-RUVAB | 303 | 11.9 |

| Model    | A   |      | B   |      | C   |     | D   |     |
|----------|-----|------|-----|------|-----|-----|-----|-----|
|          | mm  | in.  | mm  | in.  | mm  | in. | mm  | in. |
| CP4450-2 | 213 | 8.4  | 32  | 1.26 | 102 | 4.0 | 138 | 5.4 |
| CP4450-3 | 226 | 8.9  | 32  | 1.26 | 102 | 4.0 | 138 | 5.4 |
| CP4450-4 | 251 | 9.9  | 60  | 2.36 | 102 | 4.0 | 138 | 5.4 |
| CP4475-3 | 275 | 10.8 | 54  | 2.13 | 180 | 7.1 | 140 | 5.5 |
| CP4475-4 | 300 | 11.8 | 79  | 3.11 | 180 | 7.1 | 140 | 5.5 |
| CP4475-6 | 351 | 13.8 | 130 | 5.12 | 180 | 7.1 | 140 | 5.5 |


## CP4444 / CP4447 / CP4450 / CP4475

### ACCESSORIES INCLUDED

|                                    | PART NUMBER   |                  |                  |
|------------------------------------|---------------|------------------|------------------|
|                                    | CP4444-1      | CP4444<br>CP4450 | CP4447<br>CP4475 |
| • Light wire quick change retainer | 205 053 564 3 | A046095          | -                |
| • Wire quick change retainer       | -             | -                | A047095          |

### OPTIONAL ACCESSORIES

| ITEM  | CP4444  | CP4447  |
|---|---------|---------|
|   | CP4450  | CP4475  |
| 1 Zip-Quick retainer  | A046094 | -       |
| 2 Beehive retainer  | A046096 | A047096 |
| 3 Beehive retainer  | -       | A046096 |
| 4 Nail driving attachment for 20-60 penny nail size (for CP4447-RUSAB & CP4475) | -       | P042448 |




## CP4444 / CP4450

### TYPE I RIVET SETS Ø 10.2MM (.401")


| RIVET HEAD CUPPING   | 2.4MM (3/32") | 3.2MM (1/8") | 4.0MM (5/32") | 4.8MM (3/16") | 6.4MM (1/4") |
|----------------------|---------------|--------------|---------------|---------------|--------------|
| • Universal          | P089221       | P089222      | P089223       | P089224       | P089225*     |
| • Soft Blank Set     | P071108       | -            | -             | -             | -            |
| • Hardened Blank Set | P080178       | -            | -             | -             | -            |

\* Must use Light Wire Quick-Change Retainer, A046095 with these sets



### TYPE I FLUSH RIVET SETS Ø 10.2MM (.401")

|   | ØA<br>MM (IN.) | CP4444/4450<br>Ø10.2 (0.401") SHANK |
|---|----------------|-------------------------------------|
| • | 25.4 (1)       | A046090                             |
| • | 31.8 (1-1/4)   | A089232                             |
| • | 38.1 (1-1/2)   | A089233                             |
| • | 44.5 (1-3/4)   | A046091                             |




## CP4447 / CP4475

### TYPE D RIVET SETS Ø 12.7MM (.498")

| RIVET HEAD CUPPING   | 4.8MM (3/16") | 6.4MM (1/4") | 6.4MM (1/4") |
|----------------------|---------------|--------------|--------------|
| • Universal          | P089252       | P089253      | P089254*     |
| • Soft blank set     | P070995       | -            | -            |
| • Hardened blank set | P080198       | -            | -            |

\* Must use Light Wire Quick-Change Retainer, A047095



### TYPE I FLUSH RIVET SETS Ø 12.7MM (.498")

|   | ØA<br>MM (IN.) | SHANK<br>Ø12.7MM (0.498") |
|---|----------------|---------------------------|
| • | 31.8 (1-1/4)   | A047091                   |

